

Network TAP - multi-rate passive fiber TAP



Niagara Networks Modular Passive Fiber taps provide a permanent and cost effective solution to access traffic flowing across your organisations networks. They are ideal for security and network monitoring, performance analysis and other applications where multiple links need to be monitored.

The 3225 modular design can support up to 24 single width modules or 12 double width modules or any combination of single and double width modules. Each module includes high performance couplers that split the stream according to the required split ratio between the network and the monitoring port.

They ensure a complete copy of your network’s traffic reaches your security and monitoring tools with zero risk of packet loss. And because they’re passive, they require no power, therefore maintaining permanent access without introducing a single point of failure.




Front view 3225 chassis and snap-in module



LC Single Width Module

detail of LC single width Tap module



MPO Double Width Module

detail of MPO double width Tap module

Product Highlights

- Supports high density, rate transparent 1Gb, 10Gb, 25G, 40Gb or 100Gb network speeds
- Alternative to SPAN ports - collects 100% of network traffic including error packet that SPANs may drop
- 100% secure and invisible, no IP address, no MAC address, it cannot be hacked
- Plug & play, no configuration, easy installation – fully photonic, no power source required
- Compact form factor – fully modular and flexible - up to 24 TAP links

Specifications

Height (chassis)	1.72in (47mm)
Length (chassis)	9.12in (232mm)
Width (chassis)	17.57in (446mm)
Operating Temp	-40 +185°F (-40 +85°C)
Operating Humidity	-5 to 85% RH (non-condensing)
Reliability	GR-1209-CORE, GR-1221-CORE

Ordering Information

Part Number	Network	No of Taps	Module Width	Fibre Type	(Wavelength (nm))	Connector / Mode	Split Ratio	Max Insertion Loss (db)*	
								Network	Monitor
3211-S-SR-50/50	1/10 Gb	1	Single	SR, SX	850 ²	LC / Multi Mode	50/50 ¹	≤4.3	≤4.3
3213-W-SR-50/50	1/10 Gb	3	Double	SR, SX	850 ²	LC / Multi Mode	50/50 ¹	≤4.3	≤4.3
3211-S-LR-50/50	1/10/40/100 Gb	1	Single	LR4, LR, LX	1310, 1550	LC / Single Mode	50/50 ¹	≤4	≤4
3213-W-LR-50/50	1/10/40/100 Gb	3	Double	LR4, LR, LX	1310, 1550	LC / Single Mode	50/50 ¹	≤4	≤4
3211-W-SR4-50/50	40/100 Gb	1	Double	SR4 ⁴	850 ²	MPO/ Multi Mode	50/50 ¹	≤4.6	≤4.6
3212-W-SR4-50/50	40/100 Gb	2	Double	SR4 ⁴	850 ²	MPO/ Multi Mode	50/50 ¹	≤4.6	≤4.6
3211-W-SR10-50/50	100 Gb	1	Double	SR10 ⁴	850 ²	MPO/ Multi Mode	50/50 ¹	≤4.6	≤4.6
3211-W-BDSR-50/50	40 Gb	1	Double	BiDi	850	LC / Multi Mode	50/50	≤4.3	≤4.3
3211-W-PSM-50/50	40/100 Gb	1	Double	PSM ³	1310, 1550	MPO / Single Mode	50/50	≤4.2	≤4.2
3212-W-PSM-50/50	40/100 Gb	2	Double	PSM ³	1310, 1550	MPO / Single Mode	50/50	≤4.2	≤4.2
3225-PTC-2	1U rack chassis. High density passive fibre optical taps. Requires no power source to operate. Supports up to 24 tap links of single-width or up to 12 tap links of double-width or any combination of tap widths.								

* Verify your available optical budget before deploying passive taps

¹ 90/10, 80/20, 70/30, 60/40 split ratios are available

² 1310nm is available

³ 90/10, 80/20, 70/30, 60/40 split ratios are available

⁴ 70/30, 60/40 split ratios are available. Other split ratios are available upon request

About Niagara Networks

Niagara Networks provides high performance network visibility solutions for seamless administration of security solutions, performance management and network monitoring. Niagara Networks products provide advantages in terms of network operation expenses, downtime, and total cost of ownership.

A former division of Interface Masters, Niagara Networks provides all the building blocks for an advanced Visibility Adaptation Layer at all data rates up to 100Gb, including network Taps, bypass elements, packet brokers and a unified management layer.

3225 2020 Version 2



150 E Brokaw Road
San Jose, CA 95112, USA

www.niagaranetworks.com
sales@niagaranetworks.com

Tel: +1 408 622 0354
Fax: +1 408 213 7529